

MATERIAL SAFETY DATA SHEET

205M-W-018

SECTION 1

PRODUCT NAME : ELECTRIC DISCHARGE PRECESSING LIQUID SW-390

SECTION 2 PHYSICAL DATA

DESCRIPTION	CAS NO.	PERCENT
GRAPHITE POWDER		35%
DIMETHYL LAURYL AMINE OXIDE	207-04-6	30%
ALKYL AMMONIUM CHLORIDE	104-12-3	20%
SPREADER	29-60-1	10%
PHOSPHATE SALT	7664-38-2	5%

SECTION 3 PHYSICAL DATA

BOILING POINT : APPROX. 100C

VAPOR PRESSURE : NO DATA

VAPOR DENSITY(AIR-1) : LESS THAN 1

SOLUBILITY IN WATER : MISCIBLE

APPEARANCE & ODOR : ODORLESS

SPECIFIC GRAVITY(WATER=1) : 1.80

VOLATILITY BY VOLUME : NONE(EXCEPT WATER)

EVAPORATION RATE(ETHYL ETHER=1) : GREATER THAN 1

PH : 7.0

SECTION 4 FIRE & EXPLOSION HAZARD

FLASH POINT(METHOD) : NON-FLAMMABLE

LOWER EXPLOSIVE LIMIT(% IN AIR) : N/A

UPPER EXPLOSIVE LIMIT(% IN AIR) : N/A

EXTINGUISHING MEDIA : NON-FLAMMABLE

SPECIAL FIRE FIGHTING PROCEDURES : NON-FLAMMABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS : NON-FLAMMABLE